

## HD30LV

High Brightness Full HD 1080p Projector









- Bright 1080p projector 4500 ANSI lumens, perfect for brilliant big screen presentations
- 4K UHD and HDR compatible
- Easy connectivity 2x HDMI, USB Power and built in speaker
- Portable and lightweight



The HD30LV is a compact Full HD 1080p lamp projector boasting a high brightness of 4500lm. This model is designed to be used in low to high ambient light environments for gaming, TV viewing, digital entertainment and other purposes, including home office. This projector features 4K and HDR input compatible, built-in speaker, rich cinematic color, and long lamp life with a low overall cost of ownership.

## **Specifications**

The following specifications are preliminary and subject to change without notice

Display/image

DI P™ Display technology

Resolution 1080p Full HD (1920x1080)

Brightness 4,500 lumens Contrast ratio 22,000:1 Native aspect ratio 16.9 Aspect ratio - compatible 4:3 Keystone correction - vertical +/-40°

15.38 ~ 91.15Khz Horizontal scan rate 50 ~ 85(120 for 3D)Hz Vertical scan rate

Uniformity 80%

Screen size 0.76m ~ 7.65m (29.93" ~ 301.14") diagonal

Lamp info Light source type Lamp 240 Lamp watts

4000 (Bright), 15000 (Dynamic), 10000 (Eco) Lamp life hours (up to)

Optical

Throw ratio

Projection distance 1.1m - 10m / 43.31" - 393.7"

Zoom 1.1 Zoom type Manual Focal length 15.84 ~ 17.42

Native offset

Connectivity Connections

Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

General

3D

Noise level (typical) 27dB Noise level (max) 29dB

PC compatibility UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz 2D compatibility

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 4K UHD

(24/30/50/60Hz)

Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 3D compatibility

Full 3D

Security Security bar, Kensington Lock, Password protected interface OSD / display languages

25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

24/7 operation

Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

Remote control Card style 1,023BTU/hour Heat dissipation Speaker count Watts per speaker ЗW AC power cord In the box

Remote control 2x AAA Batteries Basic user manual

Input lag 8.40ms

QuickCast Pro 4K KIT Optional wireless models

Power

Power supply 100 ~ 240V, 50 ~ 60Hz

Power consumption (standby) 0.5W Power consumption (min) 210W 290W Power consumption (max)

Weight and dimensions

Dimensions (W x D x H) 316 x 244 x 108 mm / 12.44" x 9.61" x 4.25"

Gross weight 3.9 kg / 8.6 lbs 2.88 kg / 6.35 lbs Net weight UPC 796435 81 500 4



