



GPSC Series Motorized Projector Lift

X-arm projector ultra-thin electric elevator, for the new generation of projector electric elevator products, in line with international standards. Special use of small and medium-sized projectors and installation space of small environment design, such as: meeting room, training room, multimedia classroom and other places

The elevator USES x-type composite mechanical arm to lift and lower, stable operation, electronic travel positioning, one-key setting, simple operation; The hidden installation design can be integrated with the ceiling after being closed. Long-term service life design, easy maintenance and overload protection design to prevent extreme overload, effectively avoid the danger caused by extreme overload. The size of the projector is the recommended size for reference only. The actual size shall prevail.

Model					
GPSC 5015B	Product Dimensions(mm)	Net Weight(kg)	Max Projector Dimensions (With Wire And Lens)(mm)	Max Load(kg)	Power(w)
	580×580×340	28.6	440x180x480	10	145
GPSC 5010B					
GPSC 5005B	Max Travel(mm)	Precision(mm)	Noice(dB)	Voltage(v)	jib attachment(mm)
GPSC 5015	1500	< 2mm	≤55dB	220V/110V	W340xD560
GPSC 5010	Decorative Plate Dimensions(mm)	Ceiling Opening Dimensions(mm)	Angle Adjustments Up/Down/Left/Right	Dry Contact(Y/N)	
GPSC 5006	630x630	600x600	1/8/4/4	√	
	Wireless Control(Y/N)	Package + Total Product Weight (kg)	Packing Dimensions (D×W×H)mm		
	√	35	670x440x680		

Model					
GPSC 5015B	Product Dimensions(mm)	Net Weight(kg)	Max Projector Dimensions (With Wire And Lens)(mm)	Max Load(kg)	Power(w)
GPSC 5010B	580×580×255	27.2	440x180x480	12	145
GPSC 5005B	Max Travel(mm)	Precision(mm)	Noice(dB)	Voltage(v)	jib attachment(mm)
GPSC 5015	1000	< 2mm	≤55dB	220V/110V	W340xD560
GPSC 5010	Decorative Plate Dimensions(mm)	Ceiling Opening Dimensions(mm)	Angle Adjustments Up/Down/Left/Right	Dry Contact(Y/N)	
GPSC 5006	630x630	600x600	1/8/4/4	√	
	Wireless Control(Y/N)	Package + Total Product Weight (kg)	Packing Dimensions (D×W×H)mm		
	√	32.4	670x405x680		

Model					
	GPSC 5015B	Product Dimensions(mm)	Net Weight(kg)	Max Projector Dimensions (With Wire And Lens)(mm)	Max Load(kg)
	GPSC 5010B	580×580×255	23.8	440x180x480	15
GPSC 5005B		Max Travel(mm)	Precision(mm)	Noice(dB)	jib attachment(mm)
GPSC 5015		500	< 2mm	≤55dB	220V/110V
GPSC 5010		Decorative Plate Dimensions(mm)	Ceiling Opening Dimensions(mm)	Angle Adjustments Up/Down/Left/Right	Dry Contact(Y/N)
GPSC 5006		630x630	600x600	1/8/4/4	√
		Wireless Control(Y/N)	Package + Total Product Weight (kg)	Packing Dimensions (D×W×H)mm	
		√	26	670x405x680	

Model					
	Product Dimensions(mm)	Net Weight(kg)	Max Projector Dimensions (With Wire And Lens)(mm)	Max Load(kg)	Power(w)
GPSC 5015B	600×600×305	24.4	480x160x470	10	145
GPSC 5010B					
GPSC 5005B	Max Travel(mm)	Precision(mm)	Noice(dB)	Voltage(v)	jib attachment(mm)
GPSC 5015	1500	< 2mm	≤55dB	220V/110V	W360xD220
GPSC 5010	Decorative Plate Dimensions(mm)	Ceiling Opening Dimensions(mm)	Angle Adjustments Up/Down/Left/Right	Dry Contact(Y/N)	
GPSC 5006	600x600	590x590	1/8/4/4	√	
	Wireless Control(Y/N)	Package + Total Product Weight (kg)	Packing Dimensions (D×W×H)mm		
	√	29.4	650x410x640		

Model					
GPSC 5015B	Product Dimensions(mm)	Net Weight(kg)	Max Projector Dimensions (With Wire And Lens)(mm)	Max Load(kg)	Power(w)
GPSC 5010B	600×600×240	21.8	480x160x470	12	145
GPSC 5005B	Max Travel(mm)	Precision(mm)	Noice(dB)	Voltage(v)	jib attachment(mm)
GPSC 5015	1000	< 2mm	≤55dB	220V/110V	W360xD220
GPSC 5010	Decorative Plate Dimensions(mm)	Ceiling Opening Dimensions(mm)	Angle Adjustments Up/Down/Left/Right	Dry Contact(Y/N)	
GPSC 5006	600x600	590x590	1/8/4/4	√	
	Wireless Control(Y/N)	Package + Total Product Weight (kg)	Packing Dimensions (D×W×H)mm		
	√	26.6	650x365x640		

Model					
GPSC 5015B	Product Dimensions(mm)	Net Weight(kg)	Max Projector Dimensions (With Wire And Lens)(mm)	Max Load(kg)	Power(w)
GPSC 5010B	600×600×180	19.4	480x160x470	15	145
GPSC 5005B	Max Travel(mm)	Precision(mm)	Noice(dB)	Voltage(v)	jib attachment(mm)
GPSC 5015	600	< 2mm	≤55dB	220V/110V	W360xD220
GPSC 5010	Decorative Plate Dimensions(mm)	Ceiling Opening Dimensions(mm)	Angle Adjustments Up/Down/Left/Right	Dry Contact(Y/N)	
GPSC 5006	600x600	590x590	1/8/4/4	√	
	Wireless Control(Y/N)	Package + Total Product Weight (kg)	Packing Dimensions (D×W×H)mm		
	√	23.8	650x295x640		