

In-Ceiling Tab Tensioned Screen



In-Ceiling Tab Tensioned Screen

TIC-SL Series

Features:

- The flush and sleek aluminum housing integrates seamlessly in any home theater and office, providing the best concealed screen solution.
- Designed for easy installation and no drywall patching required.
- A large roller tube, a heavy weight bar and the precisely tensioned tabs work together to assure perfectly flat surface.
- Quiet tubular heavy duty motor makes the screens roll up and down smoothly.
- 23" (60cm) extra black drop to suits more different needs.

Control Systems:

- RF remote control
- Wall Control
- IR remote control(Optional)
- Built-in 12V wire trigger (Optional)
- Built-in 12V wire trigger (Optional)
- RS232 (Optional)

Surfaces available:

- Tension White 4K 1.1
- Dual Vision 4K 1.1
- Weave Acoustic HD 1.0
- Weave Acoustic 4K 1.1
- UltraSilver 3D 2.4
- Rear Pro HD 1.1

TIC-SL Series Specification

Format	Model	Size	View Area (W×H)	Border			T1	Height H1	Length L1	Bottom Shaft Length L2	Assemble Distance L3		Casing Length L4	Package Volume			GW (Kg)
				B1	B2	B3					Min	Max		PL	PW	PH	
HDTV FORMAT 16:9	TIC9092	92 "	2032 × 1143	600	60	60	60	1958	2462	2265	1862	2342	2642	2774	220	180	22.5
	TIC9094	94 "	2081 × 1171	600	60	60	60	1986	2511	2314	1911	2391	2691	2823	220	180	23.0
	TIC9100	100 "	2214 × 1245	600	60	60	60	2060	2644	2447	2044	2524	2824	2956	220	180	31.1
	TIC9106	106 "	2347 × 1320	600	60	60	60	2135	2777	2580	2177	2657	2957	3089	220	180	32.0
	TIC9110	110 "	2435 × 1370	600	60	60	60	2185	2865	2668	2265	2745	3045	3177	220	180	32.5
	TIC9112	112 "	2480 × 1395	600	60	60	60	2210	2910	2713	2310	2790	3090	3222	220	180	32.8
	TIC9120	120 "	2657 × 1495	600	60	60	60	2310	3087	2890	2487	2967	3267	3399	220	180	35.2
	TIC9125	125 "	2767 × 1556	400	60	60	60	2171	3197	3000	2597	3077	3377	3509	220	180	37.5
	TIC9135	135 "	2989 × 1681	300	60	60	60	2196	3419	3222	3019	3299	3599	3731	220	180	35.2
	TIC9150	150 "	3321 × 1868	300	60	60	60	2383	3751	3554	3351	3631	3931	4063	220	180	46.7
Cinema Scope 2.35:1	TIC2084	84 "	1963 × 835	600	60	60	60	1650	2393	2196	1793	2273	2573	2705	220	180	21.0
	TIC2092	92 "	2150 × 915	600	60	60	60	1730	2580	2383	1980	2460	2760	2892	220	180	23.8
	TIC2094	94 "	2197 × 935	600	60	60	60	1750	2627	2430	2027	2507	2807	2939	220	180	24.4
	TIC2113	113 "	2641 × 1124	600	60	60	60	1939	3071	2874	2471	2951	3251	3383	220	180	31.4
	TIC2127	127 "	2968 × 1263	400	60	60	60	1878	3398	3201	2998	3278	3578	3710	220	180	38.0
	TIC2130	130 "	3039 × 1293	300	60	60	60	1808	3469	3272	3069	3349	3649	3781	220	180	43.6
	TIC2135	135 "	3155 × 1343	300	60	60	60	1858	3585	3388	3185	3465	3765	3897	220	180	44.1
	TIC2140	140 "	3272 × 1392	300	60	60	60	1907	3702	3505	3302	3582	3882	4014	220	180	44.9
	TIC2142	142 "	3321 × 1413	300	60	60	60	1928	3751	3554	3351	3631	3931	4063	220	180	45.2
WXGA 16:10	TIC6092	92 "	1982 × 1239	600	60	60	60	2054	2412	2215	1812	2292	2592	2724	220	180	23.0
	TIC6100	100 "	2154 × 1346	500	60	60	60	2061	2584	2387	1984	2464	2764	2896	220	180	26.9
	TIC6120	120 "	2585 × 1616	400	60	60	60	2231	3015	2818	2415	2895	3195	3327	220	180	35.5
	TIC6135	135 "	2908 × 1818	300	60	60	60	2333	3338	3141	2938	3218	3518	3650	220	180	46.5
VIDEO FORMAT 4:3	TIC3100	100 "	2032 × 1524	500	60	60	60	2239	2462	2265	2062	2342	2642	2774	220	180	26.0
	TIC3120	120 "	2438 × 1829	400	60	60	60	2444	2868	2671	2468	2748	3048	3180	220	180	35.0
	TIC3150	150 "	3048 × 2286	200	60	60	75	2701	3478	3281	3078	3358	3658	3790	220	180	46.0

Measured by mm.