

[Click to Print This Page](#)



E-VISION LASER 15000 WU DIGITAL PROJECTOR

THE VISIONARIES CHOICE



E-Vision Laser 15000 WU

15,000 ISO / 13,500 ANSI Lumens | Contrast Ratio: 10,000:1 (Dynamic Black) 1,000:1 native | Part Number: 120-994

Key Specifications:

Colour System:	Blue and Red Lasers with Phosphor wheel
Display Type:	1 x 0.67" DarkChip™ DMD™
DMD Specification:	1920 x 1200 pixels native display. Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16x10
Fill Factor	
Key Features:	<p>Red Laser Assist</p> <ul style="list-style-type: none">• Uses blue and red laser diodes for increased colour fidelity and highly accurate colours <p>Video & Graphics Processing</p> <ul style="list-style-type: none">• HDMI 1.4b for Side by Side, Frame Packing, Frame Sequential & Top Bottom 3D formats.• Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources.• Triple Flash processing for 24Hz 3D input (Frame Packed and Dual Pipe 3D)• Dual Pipe Processing: Two sources in parallel for Left and Right eyes.• Synchronisation of active glasses.• 3GSDI with loop-through.• 24p and 1080p native display.• DICOM simulation mode.

Geometry Correction

- Four Corners, Vertical & Horizontal Keystone, Pincushion & Barrel, Arc and Image Rotation.
- Non Linear Warp.
- Blanking control for custom input window sizing.
- Digital zoom, pan and scan.
- Scaling available for fixed aspect ratio screens and independent input aspect ratios.

Edge Blending

- For independent edge and blend width adjustment.
- Correction for non-active pixels at the edge of the display.
- Electronic black level compensation.

Picture in Picture

- Two sources can be displayed either one within the other (PIP), or side by side, with original aspect ratios maintained.

HDBaseT® Interface

- Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from the source with low cost cabling.

Colour Processing

- Powerful seven point colour correction for accurate colour matching.
- Selectable default colour gamut

Projector Control

- Intuitive user interface for network control

PC Projector Controller Application for:

- Simultaneous control of user-defined groups of projectors
- At-a-glance monitoring of projector status
- Served web pages for browser monitoring and control access from PC's and Smart phones

Projector Automation

- Real-time clock provides daily on/off automation.

Projector Maintenance Features

- IP6x Sealed optics.
- Long life 20,000 hour illumination.

Source Compatibility

3GSDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.
HDMI including Deep Color™ processing.
Graphics standards up to 1920 x 1200 resolution at 60Hz via HDMI, DisplayPort or VGA.
Component Video (SD and HD) via RGBHV.

Inputs/Outputs

Video & Computer		
Type	Connector	Qty
DVI-D 1.0	DVI	1
DisplayPort 1.1a	DisplayPort	1
HDMI 1.4b	HDMI	2
3G-SDI in	BNC	1

3G-SDI out	BNC	1
VGA / Analog RGB	15-pin D-Sub	1
VGA Monitor out	15-pin D-Sub	1
Component Video	5 x BNC	1
HDBaseT (see LAN)	LAN RJ45	1

Communication & Control		
Type	Connector	Qty
3D Sync Out		
3D Sync In		
LAN		
RS232	BNC	1
Wired Remote	BNC	1
12V Trigger	RJ45	1
USB Power 5V/2A	9-pin D-Sub	1
	3.5mm Stereo Jack	1
NOTE: The LAN port is shared with HDBase-T.	3.5mm Stereo Jack	2
	USB Type A	1
NOTE: USB Power only for WHDI interfaces.		

3D Formats Supported	Frame Packing Dual Pipe Frame Sequential Side By Side (half) Top and Bottom								
HDTV Formats Supported	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz), 1080i (50Hz, 60Hz), 720p (50, 60Hz)								
Computer Compatibility	Up to 2560 x 1600 RB displayed within WUXGA								
Bandwidth	165 MHz on analog RGB 165 Megapixels per second on HDMI								
Remote Control	Addressable IR remote control, wireless and wired. On-Board keypad.								
Automation Control	PJLink Class 1 LAN RS-232 AMX (Device Discovery) Served web page Crestron Connected ART-NET control								
Colour Temperature	3200 to 9300K								
Operation									
illumination Type	Blue and Red Laser Light Source								
Typical illumination Life	20,000 hours								
Lenses	<table border="1"> <thead> <tr> <th>Lens</th> <th>Part No.</th> <th>Optimised Focus Range*</th> <th>Lens Shift (Frame)</th> </tr> </thead> <tbody> <tr> <td>0.38 :1 fixed</td> <td>117-341</td> <td>0.68m - 2.44m</td> <td>Depends on image</td> </tr> </tbody> </table>	Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.38 :1 fixed	117-341	0.68m - 2.44m	Depends on image
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)						
0.38 :1 fixed	117-341	0.68m - 2.44m	Depends on image						

			size, see Installation Guide.
0.75 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
0.76 :1 fixed	112-499	0.81m - 5.08m	none
1.25 - 1.79 :1 zoom	112-500	1.33m - 11.73m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
1.73 - 2.27 :1 zoom	112-501	1.83m - 14.9m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
2.22 - 3.67 :1 zoom	112-502	2.36m - 24.2m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
3.58 - 5.38 :1 zoom	112-503	3.8m - 35.35m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
5.31 - 8.26 :1 zoom	112-504	5.59m - 54.8m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame

* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,

Lens Mount	Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes
Power Requirements	200-240VAC 50/60Hz single phase 8.2A 100-130VAC 50/60Hz single phase 11.9A Note: that in 100-130VAC operation, the projector will be at 65% brightness
Power Consumption	Typical 1570W @ 240VAC in Normal mode Typical 1025W @ 110VAC in Normal mode
Thermal Dissipation	Typical 5357 BTU/Hour @ 240VAC in Normal mode Typical 3497 BTU/Hour @ 110VAC in Normal mode
Fan Noise	Normal mode: 48 dBA Max, 46 dBA Typical Eco mode: 45 dBA Max, 43 dBA Typical
Operating/Storage Temperature:	Operating: 0 to 35C (32 to 95F) Operating: 35 to 40C (95 to 104F) w/ reduced light output Storage: -20 to 60C (-4 to 140F)
Operating Humidity	10 to 90% relative, non-condensing
Weight	29.5 kg / 65 lbs

Dimensions	L: 59.83 cm x W: 50 cm x H: 21.85 cm L: 23.55 in x W: 19.68 in x H: 8.60 in						
Safety & EMC Regulations	UL / cUL, BIS, CB, CCC, KC, FCC (Part 15) Class A, FDA, CE, RoHS 2, IEC EN 60825-1-2014 Class 3R Laser Product, IEC EN 60825-1-2007 Class 1 Laser Product IEC EN 62471-5-2015 Risk Group 3						
Accessories	<table border="1"> <thead> <tr> <th>Accessory</th><th>Part No.</th></tr> </thead> <tbody> <tr> <td>Infrared Remote (replacement)</td><td>117-880</td></tr> <tr> <td>Lens Hood (Required in the USA for FDA Compliance with lenses 112-503 & 112-504)</td><td>121-867</td></tr> </tbody> </table>	Accessory	Part No.	Infrared Remote (replacement)	117-880	Lens Hood (Required in the USA for FDA Compliance with lenses 112-503 & 112-504)	121-867
Accessory	Part No.						
Infrared Remote (replacement)	117-880						
Lens Hood (Required in the USA for FDA Compliance with lenses 112-503 & 112-504)	121-867						
<p><i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i></p>							
Downloads	<p>PDF CAD Drawings</p> <p>AUTOCAD Drawings</p> <p>STEP / IGS Drawings</p> <p>Lens CAD Drawings</p>						
User Guide	<p>User Guides</p> <p>User Guides (German)</p> <p>User Guides (French)</p> <p>Laser Risk Group Document</p> <p>Important Information</p> <p>Important Information (German)</p> <p>Important Information (French)</p> <p>Control Protocol</p> <p>Ultra Short Throw Lens</p> <p>Ultra Short Throw Lens Installation Guide</p>						



DIGITAL PROJECTION, LTD



Unit 3, Aniseed Park, Broadgate,

Oldham, UK OL9 9XA



T: +44 (0)161 947 3300



www.digitalprojection.com



Specifications subject to change without notice.
©2024 Digital Projection. DLP® and Digital Light Processing™ are trademarks of Texas Instruments, Inc.



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com

A brand of  **DELTA**



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaolu 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770